

# Nextcloud

## Services

### MariaDB

#### Env

- MYSQL\_ROOT\_PASSWORD

#### Volumes

- /var/lib/mysql

#### Command

- `--transaction-isolation=READ-COMMITTED --binlog-format=ROW`

# Nextcloud

#### Env

- APACHE\_DISABLE\_REWRITE\_IP
- OVERWRITEHOST
- OVERWRITEPROTOCOL
- OVERWRITEWEBROOT
- PHP\_MEMORY\_LIMIT
- PHP\_UPLOAD\_LIMIT
- TRUSTED\_PROXIES
- PGID
- PUID
- TZ

#### Volumes

- /var/www/html
- /var/www/html/data

# Stack

```
version: '3'

services:
  db:
    image: mariadb:10.5
    restart: always
    command: --transaction-isolation=READ-COMMITTED --binlog-format=ROW
    volumes:
      - mariadb:/var/lib/mysql
    environment:
      - MYSQL_ROOT_PASSWORD=${MYSQL_ROOT_PASSWORD}
    networks:
      - nextcloud_network

  app:
    depends_on:
      - db
    image: nextcloud:latest
    restart: always
    volumes:
      - config:/var/www/html
      - ${NEXTCLOUD_DATA_PATH}:/var/www/html/data
    environment:
      APACHE_DISABLE_REWRITE_IP: 1
      OVERWRITEHOST: nextcloud.mydomain.fr
      OVERWRITEPROTOCOL: https
      OVERWRITEWEBROOT: /
      PHP_MEMORY_LIMIT: 4G
      PHP_UPLOAD_LIMIT: 10G
      TRUSTED_PROXIES: IPV4 Gateway - 10.0.3.1
      PGID: ${PGID}
      PUID: ${PUID}
      TZ: ${TZ}
    networks:
```

- proxy\_network
- nextcloud\_network

volumes:

config:

mariadb:

networks:

proxy\_network:

external: true

nextcloud\_network:

---

Revision #1

Created 2022-10-24 09:06:33 UTC by Noé Larrieu-Lacoste

Updated 2022-10-24 09:08:21 UTC by Noé Larrieu-Lacoste