

Nextcloud

Services

MariaDB

Env

- MYSQL_ROOT_PASSWORD

Volumes

- /var/lib/mysql

Command

- `--transaction-isolation=READ-COMMITTED --binlog-format=ROW`

Nextcloud

Env

- APACHE_DISABLE_REWRITE_IP
- OVERWRITEHOST
- OVERWRITEPROTOCOL
- OVERWRITEWEBROOT
- PHP_MEMORY_LIMIT
- PHP_UPLOAD_LIMIT
- TRUSTED_PROXIES
- PGID
- PUID
- TZ

Volumes

- /var/www/html
- /var/www/html/data

Stack

version: '3'

services:

db:

image: mariadb:10.5

restart: always

command: --transaction-isolation=READ-COMMITTED --binlog-format=ROW

volumes:

- mariadb:/var/lib/mysql

environment:

- MYSQL_ROOT_PASSWORD=\${MYSQL_ROOT_PASSWORD}

networks:

- nextcloud_network

app:

depends_on:

- db

image: nextcloud:latest

restart: always

volumes:

- config:/var/www/html
- \${NEXTCLOUD_DATA_PATH}:/var/www/html/data

environment:

APACHE_DISABLE_REWRITE_IP: 1

OVERWRITEHOST: nextcloud.mydomain.fr

OVERWRITEPROTOCOL: https

OVERWRITEWEBROOT: /

PHP_MEMORY_LIMIT: 4G

PHP_UPLOAD_LIMIT: 10G

TRUSTED_PROXIES: IPV4 Gateway - 10.0.3.1

PGID: \${PGID}

PUID: \${PUID}

TZ: \${TZ}

networks:

- proxy_network
- nextcloud_network

volumes:

config:

mariadb:

networks:

proxy_network:

external: true

nextcloud_network:

Revision #1

Created 24 October 2022 09:06:33 by Noé Larrieu-Lacoste

Updated 24 October 2022 09:08:21 by Noé Larrieu-Lacoste