

Nextcloud

Services

MariaDB

Env

- MYSQL_ROOT_PASSWORD

Volumes

- /var/lib/mysql

Command

- `--transaction-isolation=READ-COMMITTED --binlog-format=ROW`

Nextcloud

Env

- APACHE_DISABLE_REWRITE_IP
- OVERWRITEHOST
- OVERWRITEPROTOCOL
- OVERWRITEWEBROOT
- PHP_MEMORY_LIMIT
- PHP_UPLOAD_LIMIT
- TRUSTED_PROXIES
- PGID
- PUID
- TZ

Volumes

- /var/www/html
- /var/www/html/data

Stack

```
version: '3'

services:
  db:
    image: mariadb:10.5
    restart: always
    command: --transaction-isolation=READ-COMMITTED --binlog-format=ROW
    volumes:
      - mariadb:/var/lib/mysql
    environment:
      - MYSQL_ROOT_PASSWORD=${MYSQL_ROOT_PASSWORD}
    networks:
      - nextcloud_network

  app:
    depends_on:
      - db
    image: nextcloud:latest
    restart: always
    volumes:
      - config:/var/www/html
      - ${NEXTCLOUD_DATA_PATH}:/var/www/html/data
    environment:
      APACHE_DISABLE_REWRITE_IP: 1
      OVERWRITEHOST: nextcloud.mydomain.fr
      OVERWRITEPROTOCOL: https
      OVERWRITEWEBROOT: /
      PHP_MEMORY_LIMIT: 4G
      PHP_UPLOAD_LIMIT: 10G
      TRUSTED_PROXIES: IPV4 Gateway - 10.0.3.1
      PGID: ${PGID}
      PUID: ${PUID}
      TZ: ${TZ}
    networks:
      - proxy_network
      - nextcloud_network

volumes:
```

```
config:
```

```
mariadb:
```

```
networks:
```

```
  proxy_network:
```

```
    external: true
```

```
  nextcloud_network:
```

Revision #1

Created 2022-10-24 09:06:33 UTC by Noé Larrieu-Lacoste

Updated 2022-10-24 09:08:21 UTC by Noé Larrieu-Lacoste